

DALGAKIRAN



SINGLE AND DOUBLE STAGE RECIPROCATING AIR COMPRESSORS



STANDARD EQUIPMENT

High quality components, such as IP44 electric motors and cast iron cylinder body. Special alloy aluminium pistons and connection rod. Design in accordance with CE rules, P235GH / P265GH steel material



RELIABILITY

DALGAKIRAN reciprocating compressors have laid the foundation of the trust for the Dalgakiran brand as they had been working for many years in many different applications and industries, especially in small enterprises since 1969, when they were first produced. Dalgakiran reciprocating compressors, which are troublefree and with a long service life, may be used safely in many applications with single and double stage options.



MOTOR SAFETY SYSTEMS

- IP 44 class electric motor
- Pressure switch



COMPRESSOR BLOCK

- Cast iron cylinder body
- Aluminium injection cylinder head
- Special alloy aluminium pistons
- Special alloy aluminium connecting rod
- Cast-type pulley that provides fan-type efficient cooling
- Air suction filter
- Impact lubrication system
- Oil level gauge
- Factory-provided oil charge





SINGLE AND DOUBLE STAGE Reciprocating Air Compressors

The reciprocating compressors, produced by DALGAKIRAN Group and sold worldwide, are growing rapidly within the industry and aim for success in the global market with investments. Dalgakiran aims to be a role model in the compressed air industry by attaching importance to continuous development and customer satisfaction.

SPARE PARTS

DALGAKIRAN original spare parts extend the service life of your compressor. As it is the case with almost every manufacturer, the original spare parts of your brand undergo extensive tests and are presented in compliance with specific standards in design, production, shipment and stocking stages, which are all determined by the manufacturer.

MOTOR SAFETY SYSTEMS

- Check valve
- Belt pulley guard
- Relief valve
- Manometer
- Ready-to-operate electrical equipment



AIR TANK

- Design in accordance with CE rules,
- P235GH / P265GH steel material
- Manual drain valve
- Air outlet valve
- Impact resistant electrostatic powder paint

TECHNICAL DATA

Model	Depo / Litre	Bar	Piston Displacement L / dak.	Motor Power kW / HP	Air Connection	Dimensions (mm)			Weight kg
						Length	Width	Height	
Single-Stage Reciprocating Series									
D 2-100 D	100	8	178	1,5/2	2 x G¼"	450	1100	820	81
D 3-200 D	200	8	290	2,2/3	2 x G¼"	450	1445	965	127
D 4-300	250	8	501	3/4	1 x G¼" + 1 x G¾"	450	1745	1000	147
D 5,5-300	250	8	649	4/5,5	2 x G¼" + 1 x G¾"	450	1745	1030	180
D 5,5-500	500	8	649	4/5,5	2 x G¼" + 1 x G¾"	640	1915	1260	264
D 7,5-500	500	8	971	5,5/7,5	2 x G¼" + 1 x G¾"	640	1915	1350	283
D 10-500	500	8	1222	7,5/10	2 x G¼" + 1 x G¾"	640	1915	1370	297
D 15-500	500	8	1766	11/15	2 x G¼" + 1 x G¾"	700	1840	1520	465
Double-Stage Reciprocating Series									
D 2-100 MT	100	12,5	145	1,5/2	2 x G¼"	450	1040	820	86
D 3-200 MT	200	12,5	145	2,2/3	2 x G¼"	450	1445	965	132
D 4-300 T	250	12,5	334	3/4	1 x G¼" + 1 x G½"	450	1755	1000	167
D 5,5-300 T	250	12,5	324	4/5,5	2 x G¼" + 1 x G¾"	450	1755	1030	198
D 5,5-500 T	500	12,5	324	4/5,5	2 x G¼" + 1 x G¾"	640	1910	1255	330
D 7,5-500 T	500	12,5	647	5,5/7,5	2 x G¼" + 1 x G¾"	640	1910	1275	350
D 10-500 T	500	12,5	726	7,5/10	2 x G¼" + 1 x G¾"	640	1910	1355	365

- DALGAKIRAN compressors reserves its rights to make changes in its products and specifications without prior notice.

DALGAKIRAN