

LASER COMBINED AIR DRYER



Combined Pressure Air Dryer for
Laser Cutting Machines



7/24
HOT LINE
+90 530 280 90 36

COMBINED LASER AIR DRYER TECHNICAL DATA

- ▶ Max. Working Pressure : 16 bar (g)
- ▶ Pressure Dew Point : -70°C
- ▶ Atmospheric Dew Point : -83°C
- ▶ Airborne Water Pressure : 0,0033 gram / m³ / 7 bar (g)
- ▶ Compressed Air Remaining Oil : 0,003 gram / m³
- ▶ Compressed Air Remaining Dust : 0,01 micron
- ▶ Zero Air - Loss Drain

10 YEAR WORKING LIFE

SOLUTIONS

- 1. OPERATION** //////////////////////////////////////
Cutting air supply : ISO 8573-1 : 0-1-1
Precise cut of stainless steel up to 2 mm [14,5 bar (g)]
- 2. OPERATION** //////////////////////////////////////
Quality pressurized air supply for laser cutting machine
- 3. PERIODIC MAINTENANCE** //////////////////////////////////////
Need to change 3 air filter cartridges every 6 months, active carbon each year and desiccant dryer filling material every 5 years.

OUR COMPANY MAY CHANGE THE VALUES IN THE CATALOGUE ACCORDING TO THE RESEARCH AND DEVELOPMENT STUDIES.